

ZT22JE / ZT26JE

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Highlights

- Maintenance free lithium-ion, no noise and environmental friendly and long working shifts
- Powerful AC motor and drive system: precise, reliable and maintenance free. Works on gradeability up to 45%
- Low-temperature regenerative current control and power self-adaptive control to extend charge performance
- Multi-power charging system compatible with 10A / 16A / 32A
- New design with hood in composite material for better heat preservation, aging and corrosion resistance
- Great under-hood accessibility and large storage boxes

Features

Standard

- Horn
- Proportional control
- All motion alarm
- Flashing beacon
- Self-closing entry gate
- Emergency descent system
- Emergency stop button
- Secondary Guarding System
- Auto-leveling system
- On-board diagnostic system
- Tilt protection system
- Oscillating axle
- Load sensing system
- 4.3' Led display
- Swing-out engine tray





ZT22JE / ZT26JE

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Technical data

Model	ZT22JE	ZT26JE
Size		
Work Height	24.40m	28.70m
Platform Height	22.40m	26.70m
Horizontal Outreach	17.9m	22.1m
A - Stowed Length	10.3m	11.91m
B - Stowed Width	2.49m	2.49m
C - Stowed Height	2.76m	2.82m
D - Platform Length	2.44m	2.44m
E - Platform Width	0.91m	0.91m
F - Wheelbase	2.52m	2.80m
Tread	2.49m	2.49m
G - Ground Clearance	0.41m	0.41m
Performance		
Platform Capacity (Unrestricted/Restricted)	300/454kg	300/454kg
Drive Speed (Stowed)	5.5km/h	5.5km/h
Gradeability	45%(24°)	45%(24°)
Turning Radius (Inside)	2.72m	3.11m
Turning Radius (Outside)	5.58m	6.16m
Turntable Swing	360° continuous	360° continuous
Platform Rotation	±90°	±90°
Tail Swing	1.61m	1.61m
Jib Rotation	130° (-55°~75°)	130° (-55°~75°)
Max. Wind Speed	12.5m/s	12.5m/s
Power		
Battery	80 V	80 V
Charger	5kW / 80V	5kW / 80V
Drive Motor	4.2 kW	5.2 kW
Lifting Motor	21 kW	30 kW
Auxiliary Power	12V DC	12V DC
Hydraulic Tank Capacity	120 l	120 l
Tire		
Type	355/55-24.5 Foam-filled Tires 355/55 D625 Solid Tires	15-625 Foam-filled Tires 385/65-24 Solid Tires
Weight		
Gross	13200kg	17600kg

