

ZA32J

ARTICULATED BOOM LIFT

Comply with CE/ANSI/GB Standard

Highlights

- Increased lift capacity up to 250 Kg, 28% improved efficiency
- Built-in multiple pressure control leveling system to enhance stability
- Precise load sending system to prevent overload operations
- Deadweight Lowering System for smooth operation
- Great negative reach up to 5.7 m

Features

Standard

- Standard Features
- Horn
- All motion alarm
- Proportional control
- Self-closing entry gate
- Flashing beacon
- Auto-leveling system
- Emergency stop button
- Over tilt protection system
- Emergency descent system
- On-board diagnostic system
- Oscillating axle
- 4.3' LED display
- Load sensing system
- Swing-out engine tray
- Secondary Guarding System








ZA32J

ARTICULATED BOOM LIFT

Comply with CE/ANSI/GB Standard

Technical data

Model	ZA32J
Size	
Work Height	33.85 m
Platform Height	31.85 m
Horizontal Outreach	21.17 m
Up and Over Height	14.52 m
A - Stowed Length	12.6 m
B - Stowed Width	2.49 m
C - Stowed Height	3.1 m
D - Basket Length	2.44 m
D - Basket Length	0.91 m
Jib Length	2.44 m
F - Wheelbase	3.81 m
G - Ground Clearance	0.42 m
Performance	
Platform Capacity	250 kg
Drive Speed	5.2 km/h
Gradeability	45% (24°)
Axles Oscillation	0.2 m
Turning Radius (Inside)	7.7m / 3.3m
Turning Radius (Outside)	10.8m / 8.2m
Swing	360° continuous
Platform Rotation	±90°
H - Tail Swing	0
Max. Wind Speed	12.5 m/s
Power	
Diesel Engine	Cummins QSF2.8 54kW/2400rpm
Fuel Tank Capacity	200 l
Auxiliary Power	12 V
Control Voltage	12 V
Hydraulic System Capacity	300 l
Hydraulic Tank Capacity	200 l
Tire	
Type	445/50D710 Foam-filled tires
Weight	
Gross	19200 kg



ZOOMLION ITALIA S.r.l.
 Via Stati Uniti d'America, 26 - 20030 Senago (MI) - Italy
 Phone +39-02-990131 - info@zoomlion-italia.it - www.zoomlion-italia.it



zoomlion-italia.it

ZA32J_EN_0624