

Rough terrain

SCISSOR LIFTS

Comply with CE/ANSI/GB Standard

Highlights

- Rubber crawler provides small ground pressure and great obstacle crossing ability
- Pivot steering with good maneuverability
- Simple single handle control for steering and walking
- Work height of 8.8m with high working efficiency (ZSo610C only)
- Knuckles lubrication-free and maintenance-free
- AC motor full lifecycle maintenance-free

Features

Standard

- Proportional controls
- All motion alarm
- Fold-down handrails
- Flashing beacon
- Self-closing entry gate
- Autobrake system
- Emergency descent system
- Emergency stop button
- On-board diagnostic
- Over tilt protective system
- Horn
- Hour meter
- Extension deck (bidirectional)
- Forklift pockets
- Scissor maintenance prop
- Load sensing system
- AC power to platform





Rough terrain

SCISSOR LIFTS

Comply with CE/ANSI/GB Standard

Technical data

Model	ZS0508C	ZS0610C	ZS1216C
Size			
Work Height	6.5m	8.80m	13.8m
A Platform Height-Elevated	4.5m	6.80m	11.8m
B Platform Height-Stowed	0.99m	1.12m	1.62m
C Platform Length	1.29m	1.94m	2.3m
D Platform Width	0.7m	0.95m	1.12m
Platform Extension	0.6m	0.91m	0.91m
E Overall Height (Rails Up)	2.1m	2.26m	2.76m
Overall Height (Rails Down)	1.74m	1.77m	2.23m
F Overall Length	1.46m	2.1m	2.75m
G Overall Width	0.81m	1.05m	1.6m
H Ground Clearance	0.07m	0.127m	0.15m
Performance			
Platform Capacity	240kg	250kg	350kg
Capacity on Deck Extension	100kg	113kg	113kg
Max. Number of Workers	1	2	2
Drive Speed (Stowed)	2km/h	2km/h	2km/h
Drive Speed (Raised)	0km/h	0km/h	0km/h
Turning Radius	0m	0m	0m
Drive Motor	24V/2×0.77KW	24V/2×1.8KW	2x4KW
Up/Down Time	23/25s	34s/30s	62s/42s
Gradeability	25% (14°)	30% (17°)	30%(17°)
Max. Working Slope (Lateral/Vertical)	1.7°/1.7°	2°/2°	2°/3°
Drive	Rear Wheels	Rear Wheels	Rear Wheels
Brake	Rear Wheels	Rear Wheels	Rear Wheels
Power			
Battery	2×12V/115Ah	4×6V/220Ah 4×12V/300Ah (US)	8×6V/170Ah 8×6V/180Ah
Charger	24V/30A	24V/30A	48V/35A
Weight			
Gross	895kg	1700kg	3750kg

