

# ZS1623RT

## ROUGH TERRAIN SCISSOR LIFTS

Comply with CE/ANSI/GB Standard

### Highlights

- Strong capacity of 680kg with high working efficiency
- 4WD and axle oscillation provide great off-road capability
- One-Click leveling function
- Bilateral power system effective to lower noise
- Knuckles lubrication-free and maintenance-free
- Swing-out tray easy to service

### Features

#### Standard

- Proportional controls
- All motion alarm
- Fold-down handrails
- Flashing beacon
- Self-closing entry gate
- Autobrake system
- Emergency descent system
- Emergency stop button
- On-board diagnostic
- Overt tilt protective system
- Horn
- Hour meter
- Extension deck (bidirectional)
- Scissor maintenance prop
- Load sensing system
- AC power to platform

#### Accessories & Options

- Platform work lights
- Air line platform
- Engine heater
- Low-temperature hydraulic oil
- Synthetic biodegradable hydraulic oil





# ZS1623RT

## ROUGH TERRAIN SCISSOR LIFTS

Comply with CE/ANSI/GB Standard

### Technical data

Model	ZS1623RT
<b>Dimensions</b>	
Work Height	18m
A Platform Height-Elevated	16m
B Platform Height-Stowed	2.03m
C Platform Dimension (Length)	3.98m
D Platform Dimension (Width)	1.83m
Platform Extension	1.3m
Overall Height (Rails Up)	3.16m
E Overall Height (Rails Down)	2.47m
F Overall Length	4.88m
G Overall Width	2.3m
H Wheelbase	2.9m
I Ground Clearance	0.275m
<b>Performance</b>	
Platform Capacity	680kg
Capacity on Deck Extension	230kg
Drive Height	9m
Max. Number of Workers	4
Drive Speed (Stowed)	6.5km/h
Drive Speed (Raised)	0.5km/h
Turning Radius (Inside)	2.75m
Turning Radius (Outside)	5.8m
Up/Down Time	60/65s
Gradeability	40% (22°)
Max. Working Slope (Lateral/Vertical)	2°/3°
Drive	4WD
Tire	33×12-20/8 Solid Tire
<b>Power</b>	
Engine	Kubota v2403-M-DI
Engine Power	36kw/2600rpm
Fuel Tank Capacity	105L
Diesel Tank	100L
<b>Weight</b>	
Gross	8650kg

